

NESS+

SPORTY LOOK

With Ness+ you enjoy all the benefits of the NESS model with extra comfort thanks to co-injected temples. Using the exclusive Platinum® fog and scratch resistant coating, Ness+ is designed to enhance your work performance.

 PLATINUM®



NESSPPSI • Clear



NESSPPSF • Smoke




NESSPCSP • CSP



UNIVSTRAP (optional)
Strap only






28g

- + **ULTRA WRAP-AROUND FRAME**
- + **CO-INJECTED PC/TPR TEMPLES FOR GREATER COMFORT**
- + **PANORAMIC FIELD OF VISION**
- + ** PLATINUM® (P) SCRATCH & FOG RESISTANT COATING**
- + **NON-SLIP NOSE BRIDGE**

bolle
SAFETY

NESS+

SPORTY LOOK

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
NESS+	 Clear	NESSPPSI	IO	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/'P
	 Smoke	NESSPPSF	I3	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/'P
	 CSP	NESSPCSP	I1	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/'P
	Strap only (optional)	UNIVSTRAP	-	-	-

LENS MARKING

- 'P'. Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m²) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

Ocular lens category:

- O. Range of luminous transmittance 80–100% (Clear).
- 1. Range of luminous transmittance 43–88% (CSP).
- 3. Range of luminous transmittance 8–18% (Smoke).

FRAME MARKING

AS/NZS 1337.1:2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

TECHNOLOGIES

CSP

This innovative coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM® coating that effectively combats fogging.

PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

LENSES

- 2mm polycarbonate
- Anti-fog/anti-scratch coating on both sides of lens: Clear, Smoke and CSP
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke and CSP

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS	
LENSES	PC – 2mm – Curve 10
FRAME	-
TEMPLES	PC + TPR
STRAP (optional)	Nylon/15mm/Adjustable
SPARE LENSES	No

16/11/2018

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY